

CNB CAMERA METRIX

Type	Image	Model	Description	CCD Description	CCD Size and Type	Resolution Color	Resolution Mono	Sensitivity Color (Lux)	Sensitivity Mono	Sensitivity DSS max Color	Sensitivity DSS max Mono	True Day Night (ICR)	Number of Infra Red LED	IR Range Metre's	Auto White Balance	Auto Gain Control	Back Light Compensation	Wide Dynamic Range	OSD	Digital Zoom	Privacy Zones	SDNR	Flickerless	Lens Mount	Lens Size	Optical Zoom	RS-485	Service Video Out	Tilt-Axis Gimbal	IP Rating	Voltage	Power Consumption	Dimensions (WxHxD)	Weight
Zoom		A1568NL / A1568PL	D&N(ICR, DSS), RS-485/PTZ Controller, Dual Voltage	G5	1/4"	480	-	1	0.5	0.005	0.001	Y	-	-	Y	Y	Y	N	Y	10x	N	N	Y	-	3.3-99.0mm	30x	Y	N	N	-	24VAC/12VDC	Max.6W / 500mA	65x62x140	Approx. 375g
		A1563NL / A1563PL	D&N(ICR, DSS), RS-485/PTZ Controller	G5	1/4"	480	-	1	0.5	0.005	0.001	Y	-	-	Y	Y	Y	N	Y	10x	N	N	Y	-	3.3-99.0mm	30x	Y	N	N	-	12VDC	Max. 4.56W / 380mA	65x62x122	Approx. 330g
		AN802IR / AP802IR	D&N(ICR), RS-485	G5	1/4"	480	-	1	0	-	-	Y	7	5	Y	Y	Y	N	Y	10x	N	N	Y	-	3.5-91.0mm	26x	Y	N	N	-	12VDC	Max. 5.5W / 450mA	60.6x60.6x92.8	Approx. 300g
		AN808 / AP808	D&N(ICR), RS-485/PTZ Controller, Dual Voltage	G5	1/4"	480	-	1	0.5	-	-	Y	-	-	Y	Y	Y	N	Y	10x	N	N	Y	-	3.5-91.0mm	26x	Y	N	N	-	24VAC/12VDC	Max.6W / 500mA	60.5x60.5x114.4	Approx. 340g
		AN802 / AP802	D&N(ICR), RS-485	G5	1/4"	480	-	1	0.5	-	-	Y	-	-	Y	Y	Y	N	Y	10x	N	N	Y	-	3.5-91.0mm	26x	Y	N	N	-	12VDC	Max. 5.5W / 450mA	60.6x60.6x92.8	Approx. 300g
		A1268NL / A1268PL	D&N(DSS), Dual Voltage	G5	1/4"	480	-	1	-	0.005	0.001	N	-	-	Y	N	Y	N	Y	10x	N	N	N	-	3.9-85.8mm	22x	Y	N	N	-	24VAC/12VDC	Max. 6W / 500mA	61x58x131.9	Approx. 300g
		A1268N / A1268P	Dual Voltage	G5	1/4"	480	-	1	-	-	-	N	-	-	Y	N	Y	N	Y	10x	N	N	N	-	3.9-85.8mm	22x	Y	N	N	-	24VAC/12VDC	Max. 6W / 500mA	61x58x131.9	Approx. 300g
		A1263NL / A1263PL	D&N(DSS)	G5	1/4"	480	-	1	-	0.005	0.001	N	-	-	Y	N	Y	N	Y	10x	N	N	N	-	3.9-85.8mm	22x	Y	N	N	-	12VDC	Max. 5.4W / 450mA	61x58x114.2	Approx. 300g
		A1263N / A1263P	-	G5	1/4"	480	-	1	-	-	-	N	-	-	Y	N	Y	N	Y	10x	N	N	N	-	3.9-85.8mm	22x	Y	N	N	-	12VDC	Max. 5.4W / 450mA	61x58x114.2	Approx. 300g
		AN127L / AP127L	D&N(DSS), Dual Voltage	G5	1/4"	480	-	1	-	0.005	0.001	N	-	-	Y	N	Y	N	Y	12x	N	N	N	-	3.9-62.4mm	16x	Y	N	N	-	24VAC/12VDC	Max. 6W / 500mA	58x58x117.9	Approx. 300g
		AN127 / AP127	Dual Voltage	G5	1/4"	480	-	1	-	-	-	N	-	-	Y	N	Y	N	Y	12x	N	N	N	-	3.9-62.4mm	16x	Y	N	N	-	24VAC/12VDC	Max. 6W / 500mA	58x58x117.9	Approx. 300g
		AN122L / AP122L	D&N(DSS)	G5	1/4"	480	-	1	-	0.005	0.001	N	-	-	Y	N	Y	N	Y	12x	N	N	N	-	3.9-62.4mm	16x	Y	N	N	-	12VDC	Max. 5.4W / 450mA	58x58x103.4	Approx. 300g
		AN122 / AP122	-	G5	1/4"	480	-	0.5	-	-	-	N	-	-	Y	N	Y	N	Y	12x	N	N	N	-	3.9-62.4mm	16x	Y	N	N	-	12VDC	Max. 5.4W / 450mA	58x58x103.4	Approx. 300g
Zoom Module		M1560NL / M1560PL	D&N(ICR, DSS)	G5	1/4"	480	-	1	0.5	0.005	0.001	Y	-	-	Y	Y	Y	N	Y	10x	N	N	Y	-	3.3-99.0mm	30x	N	N	N	-	12VDC	Max. 4.56W / 380mA	48x51.6x86	Approx. 250g
		VN800 / VP800	D&N(ICR)	G5	1/4"	480	-	1	0.5	-	-	Y	-	-	Y	Y	Y	N	Y	10x	N	N	Y	-	3.5-91.0mm	26x	N	N	N	-	12VDC	Max. 4.2W / 350mA	50.5x61.1x92.25	Approx. 300g
		VN200L / VP200L	D&N(DSS)	G5	1/4"	480	-	1	-	0.005	0.001	N	-	-	Y	N	Y	N	Y	10x	N	N	N	-	3.9-85.8mm	22x	N	N	N	-	12VDC	Max. 4.2W / 350mA	49.2x53.2x86.6	Approx. 205g
		VN200 / VP200	-	G5	1/4"	480	-	0.5	-	-	-	N	-	-	Y	N	Y	N	Y	10x	N	N	N	-	3.9-85.8mm	22x	N	N	N	-	12VDC	Max. 4.2W / 350mA	49.2x53.2x86.6	Approx. 205g

Type	Image	Model	Description	CCD Description	CCD Size and Type	Resolution Color	Resolution Mono	Sensitivity Color (Lux)	Sensitivity Mono	Sensitivity DSS max Color	Sensitivity DSS max Mono	True Day Night (ICR)	Number of Infra Red LED	IR Range Metre's	Auto White Balance	Auto Gain Control	Back Light Compensation	Wide Dynamic Range	OSD	Digital Zoom	Privacy Zones	SDNR	Flickerless	Lens Mount	Lens Size	Optical Zoom	RS-485	Service Video Out	Tri-Axis Gimbal	IP Rating	Voltage	Power Consumption	Dimensions (W)(H)(D)	Weight
Box		GN608 / GP608	WDR, Free Voltage	SS2	1/3"	480	-	0.1	-	0.001	0.0003	Y	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	C/CS	-	-	Y	N	N	-	100VAC-240VAC	Max. 6W	65x59.6x122.5	Approx. 430g
		GN605 / GP605	WDR, Dual Voltage	SS2	1/3"	480	-	0.1	-	0.001	0.0003	Y	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	C/CS	-	-	Y	N	N	-	24VAC/12VDC	Max. 7.2W / 600mA	65x59.6x122.5	Approx. 430g
		GN600 / GP600	WDR	SS2	1/3"	480	-	0.1	-	0.001	0.0003	Y	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	C/CS	-	-	Y	N	N	-	12VDC	Max. 4.8W / 400mA	65x59.6x122.5	Approx. 430g
		G1818NF / G1818PF	D&N(ICR, DSS), Free Voltage	X	1/3"	550	-	0.3	0.1	0.008	0.001	Y	-	-	Y	Y	Y	N	N	2x	N	Y	Y	C/CS	-	-	N	N	N	-	100VAC-240VAC	Max. 3W	64X57.6X124.6	Approx. 430g
		G1818N / G1818P	D&N(DSS), Free Voltage	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	C/CS	-	-	N	N	N	-	100VAC-240VAC	Max. 3W	64X57.6X124.6	Approx. 430g
		G1815NF / G1815PF	D&N(ICR, DSS), Dual Voltage	X	1/3"	550	-	0.3	0.1	0.008	0.001	Y	-	-	Y	Y	Y	N	N	2x	N	Y	Y	C/CS	-	-	N	N	N	-	24VAC/12VDC	Max. 3W	64X57.6X124.6	Approx. 430g
		G1815N / G1815P	D&N(DSS), Dual Voltage	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	C/CS	-	-	N	N	N	-	24VAC/12VDC	Max. 3W	64X57.6X124.6	Approx. 430g
		G1810NF / G1810PF	D&N(ICR, DSS)	X	1/3"	550	-	0.3	0.1	0.008	0.001	Y	-	-	Y	Y	Y	N	N	2x	N	Y	Y	C/CS	-	-	N	N	N	-	12VDC	Max. 3W	64X57.6X124.6	Approx. 430g
		G1810N / G1810P	D&N(DSS)	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	C/CS	-	-	N	N	N	-	12VDC	Max. 3W	64X57.6X124.6	Approx. 430g
		G1318NF / G1318PF	D&N(ICR), Free Voltage	HQ1	1/3"	550	-	0.3	0.1	-	-	Y	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	100VAC-240VAC	Max. 2.8W	64X57.6X124.6	Approx. 430g
		G1318N / G1318P	Free Voltage	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	100VAC-240VAC	Max. 2.8W	64X57.6X124.6	Approx. 430g
		G1315NF / G1315PF	D&N(ICR), Dual Voltage	HQ1	1/3"	550	-	0.3	0.1	-	-	Y	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	24VAC/12VDC	Max. 2.8W	64X57.6X124.6	Approx. 430g
		G1315N / G1315P	Dual Voltage	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	24VAC/12VDC	Max. 2.8W	64X57.6X124.6	Approx. 430g
		G1310NF / G1310PF	D&N(ICR)	HQ1	1/3"	550	-	0.3	0.1	-	-	Y	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	12VDC	Max. 2.8W	64X57.6X124.6	Approx. 430g
		G1310N / G1310P	-	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	12VDC	Max. 2.8W	64X57.6X124.6	Approx. 430g
		G2315NF / G2315PF	D&N(ICR), Dual Voltage, Line-lock	HQ1	1/3"	550	-	0.3	0.1	-	-	Y	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	24VAC/12VDC	Max. 2.8W	64X57.6X124.6	Approx. 430g
		G2315N / G2315P	Dual Voltage, Line-lock	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	24VAC/12VDC	Max. 2.8W	64X57.6X124.6	Approx. 430g
		G2310NF / G2310PF	D&N(ICR)	HQ1	1/3"	550	-	0.3	0.1	-	-	Y	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	12VDC	Max. 2.8W	64X57.6X124.6	Approx. 430g
		G2310N / G2310P	D&N(ICR)	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	12VDC	Max. 2.8W	64X57.6X124.6	Approx. 430g
		G2965NF / G2965PF	D&N(ICR, DSS), Dual Voltage	SST	1/3"	530	-	0.3	0.2	-	0.0005	Y	-	-	Y	Y	Y	N	Y	8x	Y	Y	Y	C/CS	-	-	Y	N	N	-	24VAC/12VDC	Max. 4W / 330mA	62x58x123.8	Approx. 430g
		G2960NF / G2960PF	D&N(ICR, DSS)	SST	1/3"	530	-	0.3	0.2	-	0.0005	Y	-	-	Y	Y	Y	N	Y	8x	Y	Y	Y	C/CS	-	-	Y	N	N	-	12VDC	Max. 2.2W / 180mA	62x58x123.8	Approx. 430g
		G1965N / G1965P	D&N(DSS), Dual Voltage	SST	1/3"	530	-	0.1	-	-	0.0008	N	-	-	Y	Y	Y	N	Y	N	Y	Y	Y	C/CS	-	-	N	N	N	-	24VAC/12VDC	Max. 4W / 330mA	62x58x123.8	Approx. 430g
		G1960N / G1960P	D&N(DSS)	SST	1/3"	530	-	0.1	-	-	0.0008	N	-	-	Y	Y	Y	N	Y	N	Y	Y	Y	C/CS	-	-	N	N	N	-	12VDC	Max. 2.2W / 180mA	62x58x123.8	Approx. 430g

Box		GL3415N / GL3415P	Dual Voltage	SS11X	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	24VAC/12VDC	Max. 4W / 330mA	62x58x123.8	Approx. 430g
		GL3410N / GL3410P	-	SS11x	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	12VDC	Max. 2.8W / 240mA	62x58x123.8	Approx. 435g
		GM3005NDNF / GM3005PDNF	D&N(IR Pass Filter), Dual Voltage	SS11R	1/3"	380	-	0.1	0.05	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	24VAC/12VDC	Max. 1.7W / 130mA	62x58x93.6	Approx. 330g
		GM3005N / GM3005P	Dual Voltage	SS11R	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	24VAC/12VDC	Max. 1.7W / 130mA	62x58x93.6	Approx. 330g
		GM3000NDNF / GM3000PDNF	D&N(IR Pass Filter)	SS11R	1/3"	380	-	0.1	0.05	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	12VDC	Max. 1.7W / 130mA	62x58x93.6	Approx. 330g
		GM3000N / GM3000P	-	SS11R	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	12VDC	Max. 1.7W / 130mA	62x58x93.6	Approx. 330g
		GS3005NDNF / GS3005PDNF	D&N(IR Pass Filter), Dual Voltage	SS11R	1/3"	380	-	0.1	0.05	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	24VAC/12VDC	Max. 1.7W / 130mA	62x58x73.6	Approx. 330g
		GS3005N / GS3005P	Dual Voltage	SS11R	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	24VAC/12VDC	Max. 1.7W / 130mA	62x58x73.6	Approx. 330g
		GS3000NDVF / GS3000PDNF	D&N(IR Pass Filter)	SS11R	1/3"	380	-	0.1	0.05	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	12VDC	Max. 1.7W / 130mA	62x58x73.6	Approx. 330g
		GS3000N / GS3000P	-	SS11R	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	12VDC	Max. 1.7W / 130mA	62x58x73.6	Approx. 330g
		GS3010NBX / GS3010PBX	Monochrome, Exview CCD	B/W	1/3"	-	580	-	0.002	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	12VDC	Max. 4W / 330mA	62x58x73.6	Approx. 300g
		GS3010NB / GS3010PB	Monochrome	B/W	1/3"	-	580	-	0.003	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	C/CS	-	-	N	N	N	-	12VDC	Max. 4W / 330mA	62x58x73.6	Approx. 300g
		GN785IR / GP785IR	D&N(ICR, DSS), Dual Voltage	X	1/3"	550	-	0.3	0	0.008	0.001	Y	7	7	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8-9.5mm	-	N	N	N	-	24VAC/12VDC	Max. 4.8W / 400mA	60x55x126.9	Approx. 420g
		GN780IR / GP780IR	D&N(ICR, DSS)	X	1/3"	550	-	0.3	0	0.008	0.001	Y	7	7	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8-9.5mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	60x55x126.9	Approx. 420g
		GN735 / GP735	Dual Voltage	HQ1	1/3"	550	-	0.3	0.1	-	-	Y	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	N	N	-	24VAC/12VDC	Max. 4W / 330mA	60x55x126.9	Approx. 420g
		GN730 / GP730	-	HQ1	1/3"	550	-	0.3	0.1	-	-	Y	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	N	N	-	12VDC	Max. 2W / 150mA	60x55x126.9	Approx. 420g
		GN745 / GP745	Dual Voltage	SS11x	1/3"	480	-	0.3	-	-	-	Y	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	N	N	-	12VDC	Max. 4W / 330mA	60x55x126.9	Approx. 420g

Type	Image	Model	Description	CCD Description	CCD Size and Type	Resolution Color	Resolution Mono	Sensitivity Color (Lux)	Sensitivity Mono	Sensitivity DSS max Color	Sensitivity DSS max Mono	True Day Night (ICR)	Number of Infra Red LED	IR Range Metre's	Auto White Balance	Auto Gain Control	Back Light Compensation	Wide Dynamic Range	OSD	Digital Zoom	Privacy Zones	SDNR	Flickerless	Lens Mount	Lens Size	Optical Zoom	RS-485	Service Video Out	Ttr-Axis Gimbal	IP Rating	Voltage	Power Consumption	Dimensions (ØxH)	Weight
Dome		D1310N / D1310P	-	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	-	N	N	N	N	N	N	-	3.8mm	-	N	-	X	-	12VDC	Max. 1.8W / 150mA	85 x 76.7	Approx. 220g
		D1410N / D1410P	-	SS11x	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	-	N	N	N	N	N	N	-	3.8mm	-	N	-	X	-	12VDC	Max. 1.8W / 150mA	85 x 76.7	Approx. 220g
		D1000NDNF / D1000PDNF	D&N(ICR Pass Filter)	SS11R	1/3"	380	-	0.1	0.05	-	-	N	-	-	Y	Y	-	N	N	N	N	N	N	-	3.8mm	-	N	-	Y	-	12VDC	Max. 1.8W / 150mA	85 x 76.7	Approx. 220g
		D1000N / D1000P	-	SS11R	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	-	N	N	N	N	N	N	-	3.8mm	-	N	-	Y	-	12VDC	Max. 1.8W / 150mA	85 x 76.7	Approx. 220g
		D1715NDNF / D1715PDNF	D&N(ICR Pass Filter), Dual Voltage	NEXT	1/3"	480	-	0.3	0.1	-	-	N	-	-	Y	Y	-	N	N	N	N	N	N	-	3.8mm	-	N	-	Y	-	24VAC/12VDC	Max. 1.8W / 150mA	85 x 76.7	Approx. 220g
		D1715N / D1715P	Dual Voltage	NEXT	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	-	N	N	N	N	N	N	-	3.8mm	-	N	-	Y	-	24VAC/12VDC	Max. 1.8W / 150mA	85 x 76.7	Approx. 220g
		D1710NDNF / D1710PDNF	D&N(ICR Pass Filter)	NEXT	1/3"	480	-	0.3	0.1	-	-	N	-	-	Y	Y	-	N	N	N	N	N	N	-	3.8mm	-	N	-	Y	-	12VDC	Max. 1.8W / 150mA	85 x 76.7	Approx. 220g
		D1710N / D1710P	-	NEXT	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	-	N	N	N	N	N	N	-	3.8mm	-	N	-	Y	-	12VDC	Max. 1.8W / 150mA	85 x 76.7	Approx. 220g
		D1705N / D1705P	Dual Voltage	NEXT	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	-	N	N	N	N	N	N	-	3.8mm	-	N	-	Y	-	24VAC/12VDC	Max. 1.8W / 150mA	85 x 76.7	Approx. 220g
		D1700NDNF / D1700PDNF	D&N(ICR Pass Filter)	NEXT	1/3"	380	-	0.1	0.05	-	-	N	-	-	Y	Y	-	N	N	N	N	N	N	-	3.8mm	-	N	-	Y	-	12VDC	Max. 1.8W / 150mA	85 x 76.7	Approx. 220g
		D1700N / D1700P	-	NEXT	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	-	N	N	N	N	N	N	-	3.8mm	-	N	-	Y	-	12VDC	Max. 1.8W / 150mA	85 x 76.7	Approx. 220g
		D1010NB / D1010PB	Monochrome	B/W	1/3"	-	580	-	0.003	-	-	N	-	-	Y	Y	-	N	N	N	N	N	N	-	3.8mm	-	N	-	Y	-	12VDC	Max. 1.8W / 150mA	85 x 76.7	Approx. 220g
		D1811NVF / D1811PVF	D&N(ICR, DSS)	X	1/3"	550	-	0.3	0.1	0.008	0.001	Y	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	2.9-10mm	-	N	Y	Y	-	12VDC	Max. 3W / 250mA	85 x 104.5	Approx. 323g
		D1811NVD / D1811PVD	D&N(DSS)	X	1/3"	550	-	0.3	-	-	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	4-9mm	-	N	Y	Y	-	12VDC	Max. 3W / 250mA	85 x 104.5	Approx. 323g
		D2265NVF / D2265PVF	WDR, D&N(ICR, DSS), Dual Voltage	SS2	1/3"	480	-	0.1	-	0.001	0.0003	Y	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	-	2.9-10mm	-	Y	Y	Y	-	24VAC/12VDC	Max. 10W / 500mA	100 x 102	Approx. 366g
		D2265NVD / D2265PVD	WDR, D&N(DSS), Dual Voltage	SS2	1/3"	480	-	0.1	-	0.001	0.0003	N	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	-	4-9mm	-	Y	Y	Y	-	24VAC/12VDC	Max. 10W / 500mA	100 x 102	Approx. 366g
		D2260NVF / D2265PVF	WDR, D&N(ICR, DSS)	SS2	1/3"	480	-	0.1	-	0.001	0.0003	Y	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	-	2.9-10mm	-	Y	Y	Y	-	12VDC	Max. 6.0W / 500mA	100 x 102	Approx. 366g
		D2260NVD / D2260PVD	WDR, D&N(ICR)	SS2	1/3"	480	-	0.1	-	0.001	0.0003	N	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	-	4-9mm	-	Y	Y	Y	-	12VDC	Max. 6.0W / 500mA	100 x 102	Approx. 366g
		D2815NVF / D2815PVF	D&N(ICR, DSS), Dual Voltage	X	1/3"	550	-	0.3	0.1	0.008	0.001	Y	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	2.9-10mm	-	N	Y	Y	-	24VAC/12VDC	Max. 3W / 250mA	100 x 102	Approx. 366g
		D2815NVD / D2815PVD	D&N(DSS), Dual Voltage	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	4-9mm	-	N	Y	Y	-	24VAC/12VDC	Max. 3W / 250mA	100 x 102	Approx. 366g
		D2815N / D2815P	Dual Voltage	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8mm	-	N	Y	YY	-	24VAC/12VDC	Max. 3W / 250mA	100 x 102	Approx. 366g
		D2810NVF / D2810PVF	D&N(ICR, DSS)	X	1/3"	550	-	0.3	0.1	0.008	0.001	Y	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	2.9-10mm	-	N	Y	Y	-	12VDC	Max. 1.8W / 150mA	100 x 102	Approx. 366g
		D2810NVD / D2810PVD	D&N(DSS)	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	4-9mm	-	N	Y	Y	-	12VDC	Max. 1.8W / 150mA	100 x 102	Approx. 366g

	D2810N / D2810P	-	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8mm	-	N	Y	Y	-	12VDC	Max. 1.8W / 150mA	100 x 102	Approx. 366g
	D2315NVF / D2315PVF	D&N(ICR), Dual Voltage	HQ1	1/3"	550	-	0.3	0.1	-	-	Y	-	-	Y	Y	Y	N	N	N	N	N	Y	-	2.9-10mm	-	N	Y	Y	-	24VAC/12VDC	Max. 5W / 400mA	100 x 102	Approx. 366g
	D2315NVD / D2315PVD	Dual Voltage	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	Y	Y	-	24VAC/12VDC	Max. 5W / 400mA	100 x 102	Approx. 366g
	D2315N / D2315P	Dual Voltage	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	3.8mm	-	N	Y	Y	-	24VAC/12VDC	Max. 5W / 400mA	100 x 102	Approx. 366g
	D2310NVF / D2310PVF	D&N(ICR)	HQ1	1/3"	550	-	0.3	0.1	-	-	Y	-	-	Y	Y	Y	N	N	N	N	N	Y	-	2.9-10mm	-	N	Y	Y	-	12VDC	Max. 3W / 250mA	100 x 102	Approx. 366g
	D2310NVD / D2310PVD	-	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	Y	Y	-	12VDC	Max. 3W / 250mA	100 x 102	Approx. 366g
	D2310N / D2310P	-	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	3.8mm	-	N	Y	Y	-	12VDC	Max. 3W / 250mA	100 x 102	Approx. 366g
	D2415NVD / D2415PVD	Dual Voltage	SS11x	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	Y	Y	-	24VAC/12VDC	Max. 3W / 250mA	100 x 102	Approx. 366g
	D2415N / D2415P	Dual Voltage	SS11x	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	3.8mm	-	N	Y	Y	-	24VAC/12VDC	Max. 3W / 250mA	100 x 102	Approx. 366g
	D2410NVD / D2410P	-	SS11x	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	Y	Y	-	12VDC	Max. 1.8W / 150mA	100 x 102	Approx. 366g
	D2410N / D2410P	-	SS11x	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	3.8mm	-	N	Y	Y	-	12VDC	Max. 1.8W / 150mA	100 x 102	Approx. 366g
	D2005NVD / D2005PVD	Dual Voltage	SS11R	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	N	N	N	N	N	N	N	-	4-9mm	-	N	Y	Y	-	24VAC/12VDC	Max. 3W / 250mA	100 x 102	Approx. 366g
	D2005N / D2005P	Dual Voltage	SS11R	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	N	N	N	N	N	N	N	-	3.8mm	-	N	Y	Y	-	24VAC/12VDC	Max. 3W / 250mA	100 x 102	Approx. 366g
D2000NVD / D2000PVD	-	SS11R	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	N	N	N	N	N	N	N	-	4-9mm	-	N	Y	Y	-	12VDC	Max. 1.8W / 150mA	100 x 102	Approx. 366g	
D2000N / D2000P	-	SS11R	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	N	N	N	N	N	N	N	-	3.8mm	-	N	Y	Y	-	12VDC	Max. 1.8W / 150mA	100 x 102	Approx. 366g	
	D2965NVD / D2965PVD	D&N(DSS), Dual Voltage	SST	1/3"	530	-	0.1	-	-	0.0008	N	-	-	Y	Y	Y	N	Y	N	N	Y	Y	-	4-9mm	-	N	Y	Y	-	24VAC/12VDC	Max. 4W / 330mA	100 x 102.1	Approx. 366g
	D2965N / D2965P	D&N(DSS), Dual Voltage	SST	1/3"	530	-	0.1	-	-	0.0008	N	-	-	Y	Y	Y	N	Y	N	N	Y	Y	-	3.8mm	-	N	Y	Y	-	24VAC/12VDC	Max. 4W / 330mA	100 x 102.1	Approx. 366g
	D2960NVD / D2960PVD	D&N(DSS)	SST	1/3"	530	-	0.1	-	-	0.0008	N	-	-	Y	Y	Y	N	Y	N	N	Y	Y	-	4-9mm	-	N	Y	Y	-	12VDC	Max. 2.2W / 180mA	100 x 102.1	Approx. 366g
	D2960N / D2960P	D&N(DSS)	SST	1/3"	530	-	0.1	-	-	0.0008	N	-	-	Y	Y	Y	N	Y	N	N	Y	Y	-	3.8mm	-	N	Y	Y	-	12VDC	Max. 2.2W / 180mA	100 x 102.1	Approx. 366g
	SDN330VD / SDP330VD	Interior Design	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	N	N	-	12VDC	Less than 150mA	114 x 100	Approx. 264g
	SDN330 / SDP330	Interior Design	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	N	N	-	12VDC	Less than 150mA	114 x 100	Approx. 264g
	SDN258 / SDP258	Interior Design	SS11R	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	N	N	-	12VDC	Less than 150mA	114 x 100	Approx. 264g
	D3710N / D3710P	-	NEXT	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	N	N	N	N	N	N	N	-	3.8mm	-	N	N	Y	-	12VDC	Max. 3W / 250mA	68 x 102.1	Approx. 116g
	D3700N / D3700P	-	NEXT	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	N	N	N	N	N	N	N	-	3.8mm	-	N	N	Y	-	12VDC	Max. 3W / 250mA	68 x 102.1	Approx. 116g

Type	Image	Model	Description	CCD Description	CCD Size and Type	Resolution Color	Resolution Mono	Sensitivity Color (Lux)	Sensitivity Mono	Sensitivity DSS max Color	Sensitivity DSS max Mono	True Day Night (ICR)	Number of Infra Red LED	IR Range Metre's	Auto White Balance	Auto Gain Control	Back Light Compensation	Wide Dynamic Range	OSD	Digital Zoom	Privacy Zones	SDNR	Flickerless	Lens Mount	Lens Size	Optical Zoom	RS-485	Service Video Out	Tri-Axis Gimbal	IP Rating	Voltage	Power Consumption	Dimensions (ØxH)	Weight
Vandal-Resistant Dome		VZD207NL	22x Zoom, RS-485/PTZ, D&N(ICR, DSS), Dual Voltage	G5	1/4"	480	-	1	-	0.005	0.001	N	-	-	Y	N	Y	N	Y	10x	N	N	Y	-	3.9-85.8mm	22x	Y	Y	Y	-	24VAC/12VDC	Max. 6W / 500mA	120 x 126.5	Approx. 1.6kg
		VZD127NL	16x Zoom, RS-485/PTZ, D&N(ICR, DSS), Dual Voltage	G5	1/4"	480	-	1	-	0.005	0.001	N	-	-	Y	N	Y	N	Y	12x	N	N	Y	-	3.9-62.4mm	16x	Y	Y	Y	-	24VAC/12VDC	Max. 6W / 500mA	120 x 126.5	Approx. 1.6kg
		V1265NVF / V1265PVF	D&N(ICR, DSS), Dual Voltage	SS-2	1/3"	480	-	0.1	-	0.001	0.0003	Y	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	-	2.9-10mm	-	Y	Y	Y	IP65	24VAC/12VDC	Max. 10W / 500mA	100 x 101	Approx. 844g
		V1265NVD / V1265PVD	D&N(DSS), Dual Voltage	SS-2	1/3"	480	-	0.1	-	0.001	0.0003	N	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	-	4-9mm	-	Y	Y	Y	IP65	24VAC/12VDC	Max. 10W / 500mA	100 x 101	Approx. 844g
		V1260NVF / V1260PVF	D&N(ICR, DSS)	SS-2	1/3"	480	-	0.1	-	0.001	0.0003	Y	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	-	2.9-10mm	-	Y	Y	Y	IP65	12VDC	Max. 6.0W / 500mA	100 x 101	Approx. 844g
		V1260NVD / V1260PVD	D&N(DSS)	SS-2	1/3"	480	-	0.1	-	0.001	0.0003	N	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	-	4-9mm	-	Y	Y	Y	IP65	12VDC	Max. 6.0W / 500mA	100 x 101	Approx. 844g
		V1965NVF / V1965PVD	D&N(DSS), Dual Voltage	SST	1/3"	530	-	0.1	-	-	0.0008	N	-	-	Y	Y	Y	N	Y	N	N	Y	Y	-	4-9mm	-	N	Y	Y	IP65	24VAC/12VDC	Max. 4W / 330mA	100 x 101	Approx. 844g
		V1965N / V1965P	D&N(DSS), Dual Voltage	SST	1/3"	530	-	0.1	-	-	0.0008	N	-	-	Y	Y	Y	N	Y	N	N	Y	Y	-	3.8mm	-	N	Y	Y	IP65	24VAC/12VDC	Max. 4W / 330mA	100 x 101	Approx. 844g
		V1960NVD / V1960PVD	D&N(DSS)	SST	1/3"	530	-	0.1	-	-	0.0008	N	-	-	Y	Y	Y	N	Y	N	N	Y	Y	-	4-9mm	-	N	Y	Y	IP65	12VDC	Max. 2.2W / 180mA	100 x 101	Approx. 844g
		V1960N / V1960P	D&N(DSS)	SST	1/3"	530	-	0.1	-	-	0.0008	N	-	-	Y	Y	Y	N	Y	N	N	Y	Y	-	3.8mm	-	N	Y	Y	IP65	12VDC	Max. 2.2W / 180mA	100 x 101	Approx. 844g
		V1815NVF / V1815PVF	D&N(ICR, DSS), Dual Voltage	X	1/3"	550	-	0.3	0.1	0.008	0.001	Y	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	2.9-10mm	-	N	Y	Y	IP65	24VAC/12VDC	Max. 3W / 250mA	100 x 101	Approx. 844g
		V1815NVD / V1815PVD	D&N(DSS), Dual Voltage	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	4-9mm	-	N	Y	Y	IP65	24VAC/12VDC	Max. 3W / 250mA	100 x 101	Approx. 844g
		V1815N / V1815P	D&N(DSS), Dual Voltage	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8mm	-	N	Y	YY	IP65	24VAC/12VDC	Max. 3W / 250mA	100 x 101	Approx. 844g
		V1810NVF / V1810PVF	D&N(ICR, DSS)	X	1/3"	550	-	0.3	0.1	0.008	0.001	Y	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	2.9-10mm	-	N	Y	Y	IP65	12VDC	Max. 1.8W / 150mA	100 x 101	Approx. 844g
		V1810NVD / V1810PVD	D&N(DSS)	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	4-9mm	-	N	Y	Y	IP65	12VDC	Max. 1.8W / 150mA	100 x 101	Approx. 844g
		V1810N / V1810P	D&N(DSS)	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8mm	-	N	Y	Y	IP65	12VDC	Max. 1.8W / 150mA	100 x 101	Approx. 844g
		V1315NVF / V1315PVF	D&N(ICR), Dual Voltage	HQ1	1/3"	550	-	0.3	0.1	-	-	Y	-	-	Y	Y	Y	N	N	N	N	N	Y	-	2.9-10mm	-	N	Y	Y	IP65	24VAC/12VDC	Max. 5W / 400mA	100 x 101	Approx. 844g
		V1315NVD / V1315PVD	Dual Voltage	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	Y	Y	IP65	24VAC/12VDC	Max. 5W / 400mA	100 x 101	Approx. 844g
		V1315N / V1315P	Dual Voltage	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	3.8mm	-	N	Y	Y	IP65	24VAC/12VDC	Max. 5W / 400mA	100 x 101	Approx. 844g
		V1310NVF / V1310PVF	D&N(ICR)	HQ1	1/3"	550	-	0.3	0.1	-	-	Y	-	-	Y	Y	Y	N	N	N	N	N	Y	-	2.9-10mm	-	N	Y	Y	IP65	12VDC	Max. 3W / 250mA	100 x 101	Approx. 844g
		V1310NVD / V1310PVD	-	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	Y	Y	IP65	12VDC	Max. 3W / 250mA	100 x 101	Approx. 844g
		V1310N / V1310P	-	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	3.8mm	-	N	Y	Y	IP65	12VDC	Max. 3W / 250mA	100 x 101	Approx. 844g
		V1410NVD / V1410PVD	-	SS11x	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	Y	Y	IP65	12VDC	Max. 1.8W / 150mA	100 x 101	Approx. 844g

	V1410N / V1410P	-	SS11x	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	3.8mm	-	N	Y	Y	IP65	12VDC	Max. 1.8W / 150mA	100 x 101	Approx. 844g
 	V2265NVF / V2265PVF	D&N(ICR, DSS), Dual Voltage	SS-2	1/3"	480	-	0.1	-	0.001	0.0003	Y	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	-	2.9-10mm	-	Y	Y	Y	IP65	24VAC/12VDC	Max. 10W / 500mA	100 x 124.5	Approx. 1210g
	V2265NVD / V2265PVD	D&N(DSS), Dual Voltage	SS-2	1/3"	480	-	0.1	-	0.001	0.0003	N	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	-	4-9mm	-	Y	Y	Y	IP65	24VAC/12VDC	Max. 10W / 500mA	100 x 124.5	Approx. 1210g
	V2260NVF / V2260PVF	D&N(ICR, DSS)	SS-2	1/3"	480	-	0.1	-	0.001	0.0003	Y	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	-	2.9-10mm	-	Y	Y	Y	IP65	12VDC	Max. 6.0W / 500mA	100 x 124.5	Approx. 1210g
	V2260NVD / V2260PVD	D&N(DSS)	SS-2	1/3"	480	-	0.1	-	0.001	0.0003	N	-	-	Y	Y	Y	Y	Y	3x	Y	N	Y	-	4-9mm	-	Y	Y	Y	IP65	12VDC	Max. 6.0W / 500mA	100 x 124.5	Approx. 1210g
	V2965NVD / V2965PVD	D&N(DSS), Dual Voltage	SST	1/3"	530	-	0.1	-	-	0.0008	N	-	-	Y	Y	Y	N	Y	N	N	Y	Y	-	4-9mm	-	N	Y	Y	IP65	24VAC/12VDC	Max. 4W / 330mA	100 x 124.5	Approx. 1210g
	V2965N / V2965P	D&N(DSS), Dual Voltage	SST	1/3"	530	-	0.1	-	-	0.0008	N	-	-	Y	Y	Y	N	Y	N	N	Y	Y	-	3.8mm	-	N	Y	Y	IP65	24VAC/12VDC	Max. 4W / 330mA	100 x 124.5	Approx. 1210g
	V2960NVD / V2960PVD	D&N(DSS)	SST	1/3"	530	-	0.1	-	-	0.0008	N	-	-	Y	Y	Y	N	Y	N	N	Y	Y	-	4-9mm	-	N	Y	Y	IP65	12VDC	Max. 2.2W / 180mA	100 x 124.5	Approx. 1210g
	V2960N / V2960P	D&N(DSS)	SST	1/3"	530	-	0.1	-	-	0.0008	N	-	-	Y	Y	Y	N	Y	N	N	Y	Y	-	3.8mm	-	N	Y	Y	IP65	12VDC	Max. 2.2W / 180mA	100 x 124.5	Approx. 1210g
	V2815NVF / V2815PVF	D&N(ICR, DSS), Dual Voltage	X	1/3"	550	-	0.3	0.1	0.008	0.001	Y	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	2.9-10mm	-	N	Y	Y	IP65	24VAC/12VDC	Max. 3W / 250mA	100 x 124.5	Approx. 1210g
	V2815NVD / V2815PVD	D&N(DSS), Dual Voltage	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	4-9mm	-	N	Y	Y	IP65	24VAC/12VDC	Max. 3W / 250mA	100 x 124.5	Approx. 1210g
	V2815N / V2815P	D&N(DSS), Dual Voltage	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8mm	-	N	Y	YY	IP65	24VAC/12VDC	Max. 3W / 250mA	100 x 124.5	Approx. 1210g
	V2810NVF / V2810PVF	D&N(ICR, DSS)	X	1/3"	550	-	0.3	0.1	0.008	0.001	Y	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	2.9-10mm	-	N	Y	Y	IP65	12VDC	Max. 1.8W / 150mA	100 x 124.5	Approx. 1210g
	V2810NVD / V2810PVD	D&N(DSS)	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	4-9mm	-	N	Y	Y	IP65	12VDC	Max. 1.8W / 150mA	100 x 124.5	Approx. 1210g
	V2810N / V2810P	D&N(DSS)	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8mm	-	N	Y	Y	IP65	12VDC	Max. 1.8W / 150mA	100 x 124.5	Approx. 1210g
	V2315NVF / V2315PVF	D&N(ICR), Dual Voltage	HQ1	1/3"	550	-	0.3	0.1	-	-	Y	-	-	Y	Y	Y	N	N	N	N	N	Y	-	2.9-10mm	-	N	Y	Y	IP65	24VAC/12VDC	Max. 5W / 400mA	100 x 124.5	Approx. 1210g
	V2315NVD / V2315PVD	Dual Voltage	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	Y	Y	IP65	24VAC/12VDC	Max. 5W / 400mA	100 x 124.5	Approx. 1210g
	V2315N / V2315P	Dual Voltage	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	3.8mm	-	N	Y	Y	IP65	24VAC/12VDC	Max. 5W / 400mA	100 x 124.5	Approx. 1210g
	V2310NVF / V2310PVF	D&N(ICR)	HQ1	1/3"	550	-	0.3	0.1	-	-	Y	-	-	Y	Y	Y	N	N	N	N	N	Y	-	2.9-10mm	-	N	Y	Y	IP65	12VDC	Max. 3W / 250mA	100 x 124.5	Approx. 1210g
	V2310NVD / V2310PVD	-	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	Y	Y	IP65	12VDC	Max. 3W / 250mA	100 x 124.5	Approx. 1210g
	V2310N / V2310P	-	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	3.8mm	-	N	Y	Y	IP65	12VDC	Max. 3W / 250mA	100 x 124.5	Approx. 1210g
	V2410NVD / V2410PVD	-	SS11x	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	4-9mm	-	N	Y	Y	IP65	12VDC	Max. 1.8W / 150mA	100 x 124.5	Approx. 1210g
	V2410N / V2410P	-	SS11x	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	Y	N	N	N	N	N	Y	-	3.8mm	-	N	Y	Y	IP65	12VDC	Max. 1.8W / 150mA	100 x 124.5	Approx. 1210g

Vandal-Resistant Dome		V3816NVF / V3816VF	D&N(ICR, DSS), Dual Voltage	X	1/3"	550	-	0.3	0.1	0.008	0.001	Y	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	2.9-10mm	-	N	Y	Y	-	24VAC/12VDC	Max. 3W / 250mA	85 x 110.8	Approx. 840g
		V3811NVF / V381PVF	D&N(ICR, DSS)	X	1/3"	550	-	0.3	0.1	0.008	0.001	Y	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	2.9-10mm	-	N	Y	Y	-	12VDC	Max. 1.8W / 150mA	85 x 110.8	Approx. 840g
		V3816NVD / V3816PVD	D&N(DSS), Dual Voltage	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	4-9mm	-	N	Y	Y	-	24VAC/12VDC	Max. 3W / 250mA	85 x 110.8	Approx. 840g
		V3811NVD / V3811PVD	D&N(DSS)	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	4-9mm	-	N	Y	Y	-	12VDC	Max. 1.8W / 150mA	85 x 110.8	Approx. 840g
		V3815NF / V3815PF	D&N(ICR, DSS), Dual Voltage	X	1/3"	550	-	0.3	0.1	0.008	0.001	Y	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8mm	-	N	Y	N	-	24VAC/12VDC	Max. 1.8W / 150mA	85 x 78	Approx. 376g
		V3810NF / V3810PF	D&N(ICR, DSS)	X	1/3"	550	-	0.3	0.1	0.008	0.001	Y	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8mm	-	N	Y	N	-	12VDC	Max. 1.8W / 150mA	85 x 78	Approx. 376g
		V3815N / V3815P	D&N(DSS), Dual Voltage	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8mm	-	N	Y	N	-	24VAC/12VDC	Max. 3W / 250mA	85 x 78	Approx. 376g
		V3810N / V3810P	D&N(DSS)	X	1/3"	550	-	0.3	-	0.008	0.001	N	-	-	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8mm	-	N	Y	N	-	12VDC	Max. 1.8W / 150mA	85 x 78	Approx. 376g
		V3710N / V3710P	-	NEXT	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	N	N	N	N	N	N	N	-	3.8mm	-	N	Y	Y	-	12VDC	Max. 1.8W / 150mA	85 x 78	Approx. 376g
		V4710N / V4710P	-	NEXT	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	N	N	N	N	N	N	N	-	3.8mm	-	N	N	Y	-	12VDC	Max. 1.8W / 150mA	68 x 66.7	Approx. 570g
		V4711N / V4711P	-	NEXT	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	N	N	N	N	N	N	N	-	3.8mm	-	N	N	Y	-	12VDC	Max. 1.8W / 150mA	68 x 64.7	Approx. 265g
		V5710N / V5710P	-	NEXT	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	N	N	N	N	N	N	N	-	3.8mm	-	N	N	Y	-	12VDC	Max. 1.8W / 150mA	58 x 60	Approx. 215g
		V5711N / V5711P	-	NEXT	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	N	N	N	N	N	N	N	-	3.8mm	-	N	N	Y	-	12VDC	Max. 1.8W / 150mA	58 x 57	Approx. 215g

Type	Image	Model	Description	CCD Description	CCD Size and Type	Resolution Color	Resolution Mono	Sensitivity Color (Lux)	Sensitivity Mono	Sensitivity DSS max Color	Sensitivity DSS max Mono	True Day Night (ICR)	Number of Infra Red LED	IR Range Metre's	Auto White Balance	Auto Gain Control	Back Light Compensation	Wide Dynamic Range	OSD	Digital Zoom	Privacy Zones	SDNR	Flickerless	Lens Mount	Lens Size	Optical Zoom	RS-485	Service Video Out	Tri-Axis Gimbal	IP Rating	Voltage	Power Consumption	Dimensions (ØxH)	Weight
Var-Focal IR Dome		V2815NVR / V2815PVR	D&N(ICR, DSS), 2x D-Zoom, Vandal Resistant Dome	X	1/3"	550	-	0.3	0.1	0.008	0	Y	20	15m	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8-9.5mm	-	N	Y	N	IP65	24VAC/12VDC	Max 5W	100 x 124.5	Approx. 1210g
		V2810NVR / V2810PVR	D&N(ICR, DSS), 2x D-Zoom, Vandal Resistant Dome	X	1/3"	550	-	0.3	0.1	0.008	0	Y	20	15m	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8-9.5mm	-	N	Y	N	IP65	12VDC	Max.4.3W / 360mA	100 x 124.5	Approx. 1210g
		V1815NVR / V1815PVR	D&N(ICR, DSS), 2x D-Zoom, Vandal Resistant Dome	X	1/3"	550	-	0.3	0.1	0.008	0	Y	20	15m	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8-9.5mm	-	N	Y	N	IP65	24VAC/12VDC	Max 5W	100 x 101	Approx. 844g
		V1810NVR / V1810PVR	D&N(ICR, DSS), 2x D-Zoom, Vandal Resistant Dome	X	1/3"	550	-	0.3	0.1	0.008	0	Y	202	15m	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8-9.5mm	-	N	Y	N	IP65	12VDC	Max.4.3W / 360mA	100 x 101	Approx. 844g
		D2815NVR / D2815PVR	D&N(ICR, DSS), 2x D-Zoom	X	1/3"	550	-	0.3	0.1	0.008	0	Y	20	15m	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8-9.5mm	-	N	Y	N	-	24VAC/12VDC	Max 5W	100 x 102	Approx. 366g
		D2810NVR / D2810PVR	D&N(ICR, DSS), 2x D-Zoom	X	1/3"	550	-	0.3	0.1	0.008	0	Y	20	15m	Y	Y	Y	N	N	2x	N	Y	Y	-	3.8-9.5mm	-	N	Y	N	-	12VDC	Max.4.3W / 360mA	100 x 102	Approx. 366g
Fixed IR Dome		V2315NIR / V2315PIR	-	HQ1	1/3"	550	-	0.3	-	-	0	N	24	15m	Y	Y	Y	N	N	2x	N	N	Y	-	3.8mm	-	N	Y	Y	IP65	24VAC/12VDC	Max 5W	100 x 124.5	Approx. 1210g
		V2310NIR / V2310PIR	-	HQ1	1/3"	550	-	0.3	-	-	0	N	24	15m	Y	Y	Y	N	N	2x	N	N	Y	-	3.8mm	-	N	Y	Y	IP65	12VDC	Max.4.3W / 360mA	100 x 124.5	Approx. 1210g
		V1315NIR / V1315PIR	-	HQ1	1/3"	550	-	0.3	-	-	0	N	24	15m	Y	Y	Y	N	N	2x	N	N	Y	-	3.8mm	-	N	Y	Y	IP65	24VAC/12VDC	Max 5W	100 x 101	Approx. 844g
		V2315NIR / V2315PIR	-	HQ1	1/3"	550	-	0.3	-	-	0	N	24	15m	Y	Y	Y	N	N	2x	N	N	Y	-	3.8mm	-	N	Y	Y	IP65	12VDC	Max.4.3W / 360mA	100 x 101	Approx. 844g
		D2315NIR / D2315PIR	-	HQ1	1/3"	550	-	0.3	-	-	0	N	24	15m	Y	Y	Y	N	N	2x	N	N	Y	-	3.8mm	-	N	Y	Y	-	24VAC/12VDC	Max 5W	100 x 102	Approx. 366g
		D2310NIR / D2310PIR	-	HQ1	1/3"	550	-	0.3	-	-	0	N	24	15m	Y	Y	Y	N	N	2x	N	N	Y	-	3.8mm	-	N	Y	Y	-	12VDC	Max.4.3W / 360mA	100 x 102	Approx. 366g
		SDN258IR / SDP258IR	Space Dome Housing	SS11R	1/3"	380	-	0.1	-	-	0	N	24	15m	Y	Y	N	N	N	2x	N	N	N	-	3.8mm	-	N	N	N	-	12VDC	Max.4.3W / 360mA	114 x 100	-
Eye Ball Type IR Dome		VB2310NVR / VB2310PVR	Vandal-Resistant Housing	HQ1	1/3"	550	-	0.3	-	-	0	Y	25	15m	Y	Y	N	N	N	2x	N	N	N	-	3.8-9.5mm	-	N	N	Y	-	12VDC	Max.8.4W / 700mA	96 x 96	Approx. 848g
		VB2310NIR / VB2310PIR	Vandal-Resistant Housing	HQ1	1/3"	550	-	0.3	-	-	0	N	35	15m	Y	Y	N	N	N	2x	N	N	N	-	3.8mm	-	N	N	Y	-	12VDC	Max.8.4W / 700mA	96 x 96	Approx. 848g
		VB1710NIR / VB1710PIR	Vandal-Resistant Housing	NEXT	1/3"	480	-	0.1	-	-	0	N	25	15m	Y	Y	N	N	N	2x	N	N	N	-	3.8mm	-	N	N	Y	-	12VDC	Max.4.3W / 360mA	70 x 70	-
		VB1700NIR / VB1700PIR	Vandal-Resistant Housing	NEXT	1/3"	380	-	0.3	-	-	0	N	25	15m	Y	Y	N	N	N	2x	N	N	N	-	3.8mm	-	N	N	Y	-	12VDC	Max.4.3W / 360mA	70 x 70	-

Type	Image	Model	Description	CCD Description	CCD Size and Type	Resolution Color	Resolution Mono	Sensitivity Color (Lux)	Sensitivity Mono	Sensitivity DSS max Color	Sensitivity DSS max Mono	True Day Night (ICR)	Number of Infra Red LED	IR Range Metre's	Auto White Balance	Auto Gain Control	Back Light Compensation	Wide Dynamic Range	OSD	Digital Zoom	Privacy Zones	SDNR	Flickerless	Lens Mount	Lens Size	Optical Zoom	RS-485	Service Video Out	Tilt-Axis Gimbal	IP Rating	Voltage	Power Consumption	Dimensions (WxHxD)	Weight
Weatherproof IR Camera		BE5810NCR / BE5810PCR	D&N(ICR, DSS) IR Visible Range : 70m	X	1/3"	550	-	0.3	0.1	0.008	0	Y	126	70	Y	Y	Y	-	N	2x	N	Y	Y	-	7.5-50mm	-	N	Y	N	-	12VDC	Max. 30W / 11A	272.1 x 220.2 x 356.5	Approx. 3.2kg
		BM5562NIR / BM5562PIR	30x Zoom, D&N(ICR, DSS) IR Visible Range : 70m	G5	1/4"	480	-	1	0.5	0.005	0	Y	126	70	Y	Y	Y	-	Y	10x	N	N	Y	-	3.3-99.0mm	30x	Y	Y	N	-	12VDC	Max. 30W / 11A	272.1 x 220.2 x 356.5	Approx. 3.2kg
		BE5815NVR / BE5815PVR	D&N(ICR, DSS) IR Visible Range : 30m	X	1/3"	550	-	0.3	0.1	0.008	0	Y	34	30	Y	Y	Y	-	N	2x	N	Y	Y	-	3.8-9.5mm	-	N	Y	N	-	24VAC/12VDC	Max. 20W	123.2 x 220.2 x 356.5	Approx. 2.46kg
		BE4815NVR / BE4815PVR	D&N(ICR, DSS) IR Visible Range : 50m	X	1/3"	550	-	0.3	0.1	0.008	0	Y	56	50	Y	Y	Y	-	N	2x	N	Y	Y	-	3.8-9.5mm	-	N	Y	N	-	24VAC/12VDC	Max. 12W	110.8 x 218.6 x 325.7	Approx. 1.6kg
		BE4810NCR / BE4810PCR	Hybride IR LED, D&N(ICR, DSS) IR Visible Range : 60m	X	1/3"	550	-	0.3	0.1	0.008	0	Y	9	60	Y	Y	Y	-	N	2x	N	Y	Y	-	7.5-50mm	-	N	Y	N	-	12VDC	Max. 18W	110.8 x 218.6 x 325.7	Approx. 1.6kg
		BM4267NL / BM4267PL	22x Zoom, D&N(DSS)	G5	1/4"	480	-	1	-	0.005	-	N	-	-	Y	Y	Y	-	Y	10x	N	N	Y	-	3.9-85.8mm	22x	Y	Y	N	-	12VDC	Max. 8W	110.8 x 218.6 x 325.7	Approx. 1.65kg
		BE3815NVR / BE3815PVR	D&N(ICR, DSS) IR Visible Range : 40m	X	1/3"	550	-	0.3	0.1	0.008	0	Y	42	40	Y	Y	Y	-	N	2x	N	Y	Y	-	3.8-9.5mm	-	N	N	N	-	24VAC/12VDC	Max. 11W / 1.4A	83(Ø) x 160.4(H)	Approx. 1.1kg
		BE3315NVR / BE3315PVR	D&N(DSS) IR Visible Range : 40m	HQ1	1/3"	550	-	0.3	-	-	0	Y	42	40	Y	Y	Y	-	N	N	N	N	Y	-	3.8-9.5mm	-	N	N	N	-	24VAC/12VDC	Max. 11W / 1.4A	83(Ø) x 160.4(H)	Approx. 1.1kg
		B2815NVF / B2815PVF	D&N(ICR, DSS) IR Visible Range : 20m	X	1/3"	550	-	0.3	0.1	0.008	0	Y	18	20	Y	Y	Y	-	N	2x	N	Y	Y	-	3.8-9.5mm	-	N	N	N	IP65	24VAC/12VDC	Max. 6W	78(Ø) x 150(H)	Approx. 800g
		B2810NVF / B2810PVF	D&N(ICR, DSS) IR Visible Range : 20m	X	1/3"	550	-	0.3	0.1	0.008	0	Y	18	20	Y	Y	Y	-	N	2x	N	Y	Y	-	3.8-9.5mm	-	N	N	N	IP65	12VDC	Max. 6W	78(Ø) x 150(H)	Approx. 800g
		B2815NF / B2815PF	D&N(ICR, DSS) IR Visible Range : 30m	X	1/3"	550	-	0.3	0.1	0.008	0	Y	34	30	Y	Y	Y	-	N	N	N	Y	Y	-	12mm	-	N	N	N	IP65	24VAC/12VDC	Max. 6W	78(Ø) x 150(H)	Approx. 800g
		B2810NF / B2810PF	D&N(ICR, DSS) IR Visible Range : 30m	X	1/3"	550	-	0.3	0.1	0.008	0	Y	34	30	Y	Y	Y	-	N	N	N	Y	Y	-	12mm	-	N	N	N	IP65	12VDC	Max. 6W	78(Ø) x 150(H)	Approx. 800g
		B2315NVF / B2315PVF	D&N(DSS) IR Visible Range : 20m	HQ1	1/3"	550	-	0.3	0.1	-	0	Y	18	20	Y	Y	Y	-	N	N	N	N	Y	-	3.8-9.5mm	-	N	N	N	IP65	24VAC/12VDC	Max. 6W	78(Ø) x 150(H)	Approx. 800g
		B2310NVF / B2310PVF	D&N(DSS) IR Visible Range : 20m	HQ1	1/3"	550	-	0.3	0.1	-	0	Y	18	20	Y	Y	Y	-	N	N	N	N	Y	-	3.8-9.5mm	-	N	N	N	IP65	12VDC	Max. 6W	78(Ø) x 150(H)	Approx. 800g
		B2315N / B2315P	D&N(DSS) IR Visible Range : 30m	HQ1	1/3"	550	-	0.3	-	-	0	N	34	30	Y	Y	Y	-	N	N	N	N	Y	-	12mm	-	N	N	N	IP65	12VDC	Max. 6W	78(Ø) x 150(H)	Approx. 800g
		B2310N / B2310P	D&N(DSS) IR Visible Range : 30m	HQ1	1/3"	550	-	0.3	-	-	0	N	34	30	Y	Y	Y	-	N	N	N	N	Y	-	12mm	-	N	N	N	IP65	12VDC	Max. 6W	78(Ø) x 150(H)	Approx. 800g
		B2005N / B2005P	IR Visible Range : 30m	SS11R	1/3"	380	-	0.1	-	-	0	N	34	30	Y	Y	Y	-	N	N	N	N	Y	-	12mm	-	N	N	N	IP65	12VDC	Max. 6W	78(Ø) x 150(H)	Approx. 800g
		B2000N / B2000P	IR Visible Range : 30m	SS11R	1/3"	380	-	0.1	-	-	0	N	34	30	Y	Y	Y	-	N	N	N	N	Y	-	12mm	-	N	N	N	IP65	12VDC	Max. 6W	78(Ø) x 150(H)	Approx. 800g
		B1715N / B1715P		NEXT	1/3"	480	-	0.3	-	-	0	N	12	15	Y	Y	-	-	N	N	N	N	N	-	6mm	-	N	N	N	IP65	12VDC	Max. 4.2W / 0.3A	62(Ø) x 123(H)	Approx. 600g
		B1710N / B1710P		NEXT	1/3"	480	-	0.3	-	-	0	N	12	15	Y	Y	-	-	N	N	N	N	N	-	6mm	-	N	N	N	IP65	12VDC	Max. 4.2W / 0.3A	62(Ø) x 123(H)	Approx. 600g
		B1005N / B1005P		SS11R	1/3"	380	-	0.1	-	-	0	N	12	15	Y	Y	-	-	N	N	N	N	Y	-	6mm	-	N	N	N	IP65	12VDC	Max. 4.2W / 0.3A	62(Ø) x 123(H)	Approx. 600g
		B1000N / B1000P		SS11R	1/3"	380	-	0.1	-	-	0	N	12	15	Y	Y	-	-	N	N	N	N	Y	-	6mm	-	N	N	N	IP65	12VDC	Max. 4.2W / 0.3A	62(Ø) x 123(H)	Approx. 600g

Type	Image	Model	Description	CCD Description	CCD Size and Type	Resolution Color	Resolution Mono	Sensitivity Color (Lux)	Sensitivity Mono	Sensitivity DSS max Color	Sensitivity DSS max Mono	True Day Night (ICR)	Number of Infra Red LED	IR Range Metre's	Auto White Balance	Auto Gain Control	Back Light Compensation	Wide Dynamic Range	OSD	Digital Zoom	Privacy Zones	SDNR	Flickerless	Lens Mount	Lens Size	Optical Zoom	RS-485	Service Video Out	Tri-Axis Gimbal	IP Rating	Voltage	Power Consumption	Dimensions (Ø)x(H)	Weight
Specialty Camera		SD1710NA / SD1710PA	Smoke Detector Type, Audio Function	NEXT	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	N	-	N	N	N	N	N	-	3.8mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	89.5 x 63	Approx. 153g
		SD1710N / SD1710P	Smoke Detector Type	NEXT	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	N	-	N	N	N	N	N	-	3.8mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	89.5 x 63	Approx. 153g
		SD1700NA / SD1700PA	Smoke Detector Type, Audio Function	NEXT	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	N	-	N	N	N	N	N	-	3.8mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	89.5 x 63	Approx. 153g
		SD1700N / SD1700P	Smoke Detector Type	NEXT	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	N	-	N	N	N	N	N	-	3.8mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	89.5 x 63	Approx. 153g
		CN330IR / CP330IR	BusTop Cam(for Vehicle)	HQ1	1/3"	550	-	0.3	0	-	-	N	11	10	Y	Y	N	-	N	N	N	N	N	-	2.45mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	95.2(W) x 55.4(H) x 47.7(D)	-
		CN258IR / CP258IR	BusTop Cam(for Vehicle)	SS11R	1/3"	380	-	0.1	0	-	-	N	11	10	Y	Y	N	-	N	N	N	N	N	-	2.45mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	95.2(W) x 55.4(H) x 47.7(D)	-
		SN330IR / SP330IR	Sensor Cam	HQ1	1/3"	550	-	0.3	0	-	-	N	11	10	Y	Y	N	-	N	N	N	N	N	-	3.8mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	80(W) x 42(H) x 47.7(D)	-
		SN258IR / SP258IR	Sensor Cam	SS11R	1/3"	380	-	0.1	0	-	-	N	11	10	Y	Y	N	-	N	N	N	N	N	-	3.8mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	80(W) x 42(H) x 47.7(D)	-
		BN258IR	Bullet Type	SS11R	1/3"	380	-	0.1	0	-	-	N	9	7	Y	Y	N	-	N	N	N	N	N	-	6mm	-	N	N	N	IP66	12VDC	Max. 2W	36 x 77.9	-
		BN258ST	Bullet Type	SS11R	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	N	-	N	N	N	N	N	-	6mm	-	N	N	N	IP66	12VDC	Max. 2W	36 x 77.9	-
		MN1310VD / MP1310VD	-	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	-	N	N	N	N	Y	-	4-9mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	43(W) x 43(H)	-
		MN1310 / MP1310	-	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	-	N	N	N	N	Y	-	3.8mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	43(W) x 43(H)	-
		MN1310P / MP1310P	Pinhole Cone Type Lens	HQ1	1/3"	550	-	0.3	-	-	-	N	-	-	Y	Y	Y	-	N	N	N	N	Y	-	3.8mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	43(W) x 43(H)	-
		MN258VD / MP258VD	-	SS11R	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	Y	-	N	N	N	N	Y	-	4-9mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	43(W) x 43(H)	-
		MN258 / MP258	-	SS11R	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	Y	-	N	N	N	N	Y	-	3.8mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	43(W) x 43(H)	-
		MN258P / MP258P	Pinhole Cone Type Lens	SS11R	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	Y	-	N	N	N	N	Y	-	3.8mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	43(W) x 43(H)	-
	 	MN1710 / MP1710	-	HQ1	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	Y	-	N	N	N	N	N	-	3.8mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	39(W) x 37(H) x 34.6(D)	-
		MN1710P / MP1710P	Pinhole Cone Type Lens	HQ1	1/3"	480	-	0.3	-	-	-	N	-	-	Y	Y	Y	-	N	N	N	N	N	-	Pinhole Lens	-	N	N	N	-	12VDC	Max. 3W / 250mA	39(W) x 37(H) x 34.6(D)	-
		MN1700 / MP1700	-	HQ1	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	Y	-	N	N	N	N	N	-	3.8mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	39(W) x 37(H) x 34.6(D)	-
		MN1700P / MP1700P	Pinhole Cone Type Lens	HQ1	1/3"	380	-	0.1	-	-	-	N	-	-	Y	Y	Y	-	N	N	N	N	N	-	Pinhole Lens	-	N	N	N	-	12VDC	Max. 3W / 250mA	39(W) x 37(H) x 34.6(D)	-
		MN1010B	-	B/W	1/3"	-	380	0.1	-	-	-	N	-	-	Y	Y	Y	-	N	N	N	N	N	-	3.8mm	-	N	N	N	-	12VDC	Max. 3W / 250mA	39(W) x 37(H) x 34.6(D)	-
		MN1010BP / MP1010BP	Pinhole Cone Type Lens	B/W	1/3"	-	380	0.1	-	-	-	N	-	-	Y	Y	Y	-	N	N	N	N	N	-	Pinhole Lens	-	N	N	N	-	12VDC	Max. 3W / 250mA	39(W) x 37(H) x 34.6(D)	-